



Acoustifoam™ FLAT PANELS Data Sheet

The Acoustifoam™ FLAT PANELS are lightweight, dimensionally sized panels, that are available in multiple thicknesses to enable tight sound specification control to ensure optimal sound absorption is designed for the space. With multiple fastening methods, and Best in Class absorption per inch, it is easy to see how the FLAT PANELS out deliver the competition within the acoustic design space. Though typically used in applications above shoulder height where impact is less likely, or in large volume ‘acoustic spaces’ (studios, theaters, conference rooms, artistic installations, etc.), there is no question that the FLAT PANELS provide the achievable results they tout.



Standard thicknesses: 1", 1.5", 2", 3"

Standard sizes: 2'x2', 2'x4', 4'x4', 4'x8'

[* ‘custom’ sizes and shapes available]

NRC:

Sound Absorption Coefficient [Sabins / ft ²]										
Finish	Thickness [in]	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SAA	NRC	Mounting Type
Natural White	1.00	0.11	0.16	0.53	0.85	0.99	1.04	0.63	0.65	A
	1.50	0.17	0.28	0.84	0.99	1.03	1.04	0.78	0.80	A
	2.00	0.23	0.48	1.08	1.19	1.16	1.11	0.97	1.00	A
	3.00	0.45	0.87	1.26	1.07	1.06	1.10	1.05	1.05	A
	4.00	0.58	1.19	1.45	1.38	1.29	1.24	1.34	1.35	A

Quick Ship colors:

White	Sea Grey	Sand	Red	Pewter	Khaki	Deep Blue	Dk. Bronze	Bright Blue	Black

NOTE: **Pantone Custom Coloring** (‘PCC’) is available on ALL products (certain minimums are required)

Installation:

Adhesive, clips, Velcro, etc. (see ‘Acoustifoam FLAT PANELS Installation Instructions’)

Décor Acoustics
 5403 Western Ave #C
 Boulder, CO 80301
www.DecorAcoustics.com
 720-449-3063