



Acoustifoam™ TILES Data Sheet

Our Acoustifoam™ TILES bring our highly customizable and acoustic absorptive material really into the realm of “design”. Available in 10 standard patterns, these large format tiles come in either a natural white color, one of 10 Quick Ship colors, or can further be color customized through our Pantone Custom Coloring (PCC). Touting an NRC rating of 0.70 (compare to 0.25 for 7mm felt), Acoustifoam Tiles provide truly decorative sound absorption without the need of adding chemicals to achieve an acceptable fire rating.

Zion	Facet	Trestle	Waffle	TOPO
Thatch	Atomic	Rhythmic	Flower	Everest

Size:

23" x 23" - for Direct application

23-1/2" x 23-1/3" - for 'drop-in' applications)

(Note: thickness ranges between 1-1/2" -3" depending on specific design; inquire for specific design)

NRC: 0.70

Sound Absorption Coefficient [Sabins / ft ²]										
Finish	Thickness [in]	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SAA	NRC	Mounting Type
	2.00	0.05	0.19	0.66	0.90	1.01	1.08	0.69	0.70	A

Quick Ship colors:

White	Sea Grey	Sand	Red	Pewter	Khaki	Deep Blue	Dk. Bronze	Bright Blue	Black

NOTE: Pantone Custom Coloring ('PCC') is available on ALL products (certain minimums are required)

Installation:

Adhesive, clips, Velcro, etc. (see 'Acoustifoam TILES Installation Instructions')